

**Conductoare din otel-zincat, conform BS 183-1972**  
**Galvanized Steel Wire Strand, according to BS 183-1972**

<b>Constructie</b> <i>Construction</i>		<b>Diametru</b> <b>conductor</b>	<b>Fora de rupere minima</b> <i>Minimum Breaking Load</i>			<b>Masa</b> <b>conductorulu</b>
<i>Numar</i> <b>sarme</b> <i>No. of</i> <b>wires</b>	<i>Diametru</i> <b>sarma</b> <i>Wire</i> <b>diameter</b> <b>m</b>	<i>Overall</i> <b>diameter</b> <b>mm</b>	<b>Grad</b> <i>Grade</i> <b>1000</b> <b>N</b>	<b>Grad</b> <i>Grade</i> <b>1150</b> <b>N</b>	<b>Grad</b> <i>Grade</i> <b>1300</b> <b>N</b>	<b>Conductor</b> <b>Weight</b> <b>kg/km</b>
7	1.00	3.0	5500	6320	7150	43
7	1.25	3.8	8550	9880	11150	67
7	1.40	4.2	10750	12350	14000	84
7	1.60	4.8	14100	16200	18300	110
7	1.80	5.4	17800	20500	23200	140
7	2.00	6.0	22000	25300	28600	170
7	2.36	7.1	30600	35200	39800	240
7	2.65	8.0	38600	44400	50200	300
7	3.00	9.0	49500	56900	64300	392
7	3.15	9.5	54550	62750	70900	430
7	3.25	9.8	58050	66800	75500	460
7	3.65	11.0	73250	84200	95200	570
7	4.00	12.0	88000	101000	114000	690
7	4.25	12.8	99300	114000	129000	780
7	4.75	14.0	124000	142700	161300	970
19	1.00	5.0	14920	17160	19400	120
19	1.25	6.3	23320	26810	30310	180
19	1.40	7.0	29250	33640	38020	230
19	1.60	8.0	38200	43930	49660	300
19	2.00	10.0	59690	68640	77600	470
19	2.50	12.5	93270	107300	121300	730
19	3.00	15.0	134300	154500	174600	1050
19	3.55	17.8	188000	216300	244500	1470
19	4.00	20.0	238700	274600	310400	1870
19	4.75	23.8	336700	387200	437700	2630